

# TANKER CALIBRATION CHART

TANK CALIBRATED BY COAST INSTRUMENT & PUMP ENGINEERS.

(On Horse DAFKBL 440 V)

VEHICLE OWNED BY: A. A. Transporters Ltd.  
MAKE AND REGISTRATION No. Semi Trailer ZD 0189

P.O. BOX 86086  
PHONE: 0725 94446  
MOMBASA

181.25 (1) COMPARTMENT CAPACITY DIP CM. CU. METER		207.45 Compartment (2) Dip Cm. Capacity Cu.Meter		207.6 COMPARTMENT (3) CAPACITY DI CM CU. METER	
16.05	1.00	20.3	1.00	20.9	1.00
28.75	2.00	33.0	2.00	34.9	2.00
40.0	3.00	43.9	3.00	48.3	3.00
51.05	4.00	54.45	4.00	61.1	4.00
61.7	5.00	64.9	5.00	73.5	5.00
72.45	6.00	75.4	6.00	85.9	6.00
83.0	7.00	85.75	7.00	98.2	7.00
93.35	8.00	96.1	8.00	110.7	8.00
104.0	9.00	106.05	9.00	123.05	9.00
109.6	9.50	116.2	10.00	129.7	9.50
114.6	10.00	126.45	11.00	135.85	10.00
120.2	10.50	131.7	11.50	142.6	10.50
125.5	11.00	136.8	12.00	149.1	11.00
131.1	11.50	142.05	12.50	155.6	11.50
136.6	12.00	147.6	13.00	162.3	12.00
139.65	12.25	152.75	13.50	165.75	12.25
142.65	12.50	158.2	14.00	169.6	12.50
145.8	12.75	164.0	14.50	173.7	12.75
149.25	13.00	167.0	14.75	178.2	13.00
152.9	13.25	169.9	15.00	183.6	13.25
157.25	13.50	173.3	15.25	185.1	13.30
158.15	13.55	176.9	15.50	186.5	13.35
159.25	13.60	180.8	15.75	188.1	13.40
160.2	13.65	185.8	16.00	189.85	13.45
161.3	13.70	187.0	16.05		
162.65	13.75	188.55	16.10		
163.9	13.80	190.65	16.15		
165.5	13.85	192.2	16.20		

CALIBRATION CHARTS WITH APPROPRIATE DIP STICKS ARE THE GUIDANCE FOR LOADING AND OFF-LOADING PRODUCTS AT BONDED OIL INSTALLATIONS. METER WHICH IS CALIBRATED AND SEALED BY THE WEIGHTS & MEASUREMENTS DEPARTMENT BE USED TO VERIFY.

N.B. Line "T." MUST be level with tube top when taking dip.

Volume based at 20°C.

17/06/2010 (U-M) 0215

